

NetBeans Platform

Tom Wheeler

11/11/09

SIUE :: November 2009

Intro: What I Cover in this Section

- Limitations of Java's FileSupport
- NetBeans FileSystem API
 - ◇ How it improves on Java's file support
 - ◇ How to use it
- NetBeans System FileSystem
- Layer Files and configuration

File Access in Java

- Java represents files via `java.io.File`
 - ◇ Can represent either a file or directory
- I/O with files in Java
 - ◇ `FileOutputStream` to write
 - ◇ `FileInputStream` to read

Problems with java.io.File

- java.io.File has some limitations
 - ◇ Files assumed to exist only “on disk”
 - ◇ File may or may not actually exist
 - ◇ No support for event notification
- Some of this is addressed in JSR 203
 - ◇ Expected to be in Java 7
- NetBeans FileSystems API solves it now!

FileSystem API Features

- Support for “virtual” files
 - ◇ On-disk
 - ◇ On a remote server
 - ◇ An element in an XML document
 - ◇ A record in a database
- Support for event notification
 - ◇ Create/change/delete/rename

FileSystem API Features (2)

- Support for attributes (metadata)
 - ◇ Can get/set arbitrary values on FileObject
- Support for file locking
 - ◇ Works fine, though somewhat inefficient
- Support for various filesystems
 - ◇ e.g. on-disk, XML, ZIP file, memory-based
 - ◇ Could also create your own
- Each FileObject has input/output streams

FileSystem API Overview

- FileSystem class
 - ◇ Represents entire filesystem
 - ◇ Typically hierarchical (like UNIX)
 - ◇ FileSystem has a root (like UNIX)
 - ◇ Provides access to individual FileObjects

FileSystem API Overview (2)

- FileObject class
 - ◇ Represents single item in file system
 - ◇ Could be a file or a folder (container)
 - ◇ Must exist in the filesystem
 - ◇ Unlike java.io.File
 - ◇ Allows deletion and creation of children
 - ◇ Has a MIME type

FileSystem API Overview (3)

□ FileObject IO

◇ Write to FileObject

- ◇ Use its OutputStream

◇ Read from FileObject

- ◇ Use its InputStream
- ◇ Use new convenience methods
 - asBytes() / asLines() / asText()

□ FileObjects just represent bits

- ◇ Not information, just raw data

FileSystem API Examples

```
FileSystem memFs = FileUtil.createMemoryFileSystem();
FileObject root = memFs.getRoot();
FileObject memFolder = root.createFolder("myfolder");
FileObject memFileObj = memFolder.createData("myfile.txt");

// we can get the same file like this
FileObject same = root.getFileObject("myfolder/myfile.txt");

// get the file extension (returns "txt")
String extension = same.getExt();

// get the file's base name (returns "myfile")
String basename = same.getName();

// get the file's name and extension (returns "myfile.txt")
String nameAndExt = same.getNameExt();

// get the complete path (returns "myfolder/myfile.txt")
String path = same.getPath();
```

System FileSystem

- NetBeans has a special filesystem
 - ◇ Called the "System FileSystem"
 - ◇ It's a registry for configuration information
 - ◇ Roughly analogous to MS Windows registry
 - ◇ Or the /etc directory on a UNIX system
 - ◇ Used to configure many aspects of NB
 - ◇ Menus, toolbars, keybindings
 - ◇ Editor settings and app. preferences

Demo: Examine System FileSystem

- You can see the SysFS from the IDE
 - ◇ Expand a module project
 - ◇ It must have a layer file for this to work
 - ◇ Expand “Important Files”
 - ◇ Expand “<this layer in context>”
- Let's examine the contents...

Layer Files

- NB Platform is declarative
- A module may contain a layer file
 - ◇ A file in XML format
 - ◇ Conforms to a DTD
 - ◇ Referenced in module's manifest
 - ◇ It's XML-based
 - ◇ Self-describing and human-readable
- Not all modules have (or need) them

Layer Files (2)

- A layer file is a “slice” of the SysFS
 - ◇ Allows a module to contribute content
 - ◇ May add new items
 - ◇ May modify or remove existing items
 - ◇ Which were added in other modules
 - ◇ Hence “this layer in context”

How Layer Files and SysFS Work

- NB Platform starts up
- NB Platform finds all layer files
- XML Layers are merged
 - ◇ With a writable filesystem
 - ◇ Result is actual filesystem on disk
- NetBeans Platform opens
 - ◇ You can see the result of the merge
 - ◇ Windows/toolbars/menus/etc. reflect change

Layer File Examples

□ Add to a folder

```
<filesystem>  
  <folder name = "Menu">  
    <file name = "My New Menu"/>  
  </folder>  
</filesystem>
```

□ Delete from a folder

```
<filesystem>  
  <folder name = "Menu">  
    <file name="Help_hidden"/>  
  </folder>  
</filesystem>
```


Layer File and SysFS Demo

- I'll create a new action using wizard
 - ◇ This will add/modify layer file for my module
 - ◇ We'll examine the change
 - ◇ We'll run the app
 - ◇ We'll modify the layer entry
 - ◇ And run the app to see the effect

Programmatic Interaction with SysFS

- You can access SysFS from your app:

```
// to get the SysFS root  
FileUtil.getConfigRoot()
```

```
// to get a specific folder  
FileUtil.getConfigFile("Menu");
```

- Then use FS API methods to read it
- The System FileSystem is writable
 - ◇ You can even modify it at runtime
 - ◇ See developer FAQ on Wiki for example

Review Questions

- Name two limitations of `java.io.File`
- What are two classes in File System API?
- Name three types of filesystems
- What is the System File System?
- What is a layer file?
- How can you view SysFS in the IDE?

Recap

- Java's file support has limitations
- FileSystem API in NB improves on this
 - ◇ Supports disk, RAM and other storage
 - ◇ Support for file locking and notification
- System FileSystem used for configuration
 - ◇ Layer files are merged at runtime
 - ◇ Layer files can add/modify/remove things

Exercise (30 minutes)

- Create an application which prints the contents of the System Filesystem
 - ◇ I will help you get started
 - ◇ We'll do these together
 - ◇ Create new app and add a module to it
 - ◇ Add dependency on FileSystem API
 - ◇ Create/register an action
 - ◇ You will then add the logic to print it out